



TEAK OIL

DIF-OTK

DESCRIPTION

Teak oil is a quick drying oil for surface treatment of dark types of wood. It provides a good depth in the structure of the wood and a fairly good resistance against the influence from water, coffee, alcohol. It has a high UV resistance.

PRINCIPLE CHARACTERISTICS

Used on Furniture & other indoor & Outdoor equipment of dark types of wood where an open grain finish is desired.

BASIC DATA AT 25°C

Drying Time

3-4 hours ; through dry: 24 hours

Flash Point

< 21°C

Specific Gravity

0.9

Solid Content

63% by weigh; 58% by volume

Mixing Ratio

Ready for use

Thinner

White spirit

Coverage

15-20m² per LT

RECOMMENDED SUBSTRAT CONDITION AND TEMPERATURES

- Wood should be dry & clean from any contamination.
- Prepared wood.

CLEAN-UP

Clean hands and tools immediately with NC thinner.
Clean spills right away with a damp cloth.

APPLICATION

Rag or plush Pad

DIRECTION FOR USE

INSTRUCTION

The last sanding should be carried out with sand paper coarser than NO.150. The oil is applied with cloth or plush pad across the structure of wood.

The wood should absorb as much oil as possible, No puddle of oil should remain after the treatment.

After 24 hours of drying a second coat of oil is applied and sanding is carried out with sanding paper No 320 or steel wool No.00.

Sand paper gives a matt appearance while steel work gives a silk matt surface (immediately after the wet sanding surface is wiped off carefully with a cloth.)

If a more ample finish is required, the treatment can be repeated after 3-4 hours.

The resistance to water alcohol is dependant on the fullness of the treatment

SAFETY AND HEALTH

In case of eye contact treat any foreign body by flushing with large amounts of water .

For skin contact repeated exposure may cause skin dryness or cracking since , it contains cobalt, ketoxime may cause allergic reaction.

For safety when applying it is advisable to wear eye protection glasses hand gloves and face mask.

Keep out of the reach of children , do not use or store by hanging on a hook.

Lead to toxic exposure that cause serious damage for brain especially for children and pregnant women.

SHIPPING

Packing

US Gallon – 4 L

Storage Condition

Store away from extreme temperature.
Containers should be kept closed during storage.

Limitations

Avoid inhalation of spray mist or vapor as well as the contact between the wet paint and exposed skin or eyes period.

