



MSDS

QUICK DRY PAINT

Extreme fast drying, solvent based paint.

BMA PAINTS for commercial and industry – NAHR EL MOTT – LEBANON

Telephone: 00961(1)885385/485 – Fax: 00961(1)885685 – P.O. Box: 55091

E-mail: info@bmapaints.com / customerservice@bmapaints.com

Website: www.bmapaints.com

STABILITY AND CHEMICAL REACTIVITY:

- This product is relatively stable.
- This product doesn't thermal – decompose if it's used and stored according to the specifications.
- Hazardous polymerization is not expected.
- Hazardous decomposition of this product may release CO₂, CO, NO, NO₂, and Small amount of hydrocarbons.
- This product does not self-ignite.
- This product is incompatible with strong oxidizing agents, acids and alkalis.

COMPONENTS:

Component	% by weight	C.A.S. #
B. G.	0 – 2 %	111-76-2
Resins	40 – 55 %	N.R.
Additives	4 – 7 %	N.R.
Xylene	20 – 25 %	1330-20-7
charges	10 – 15 %	N.R.
Butyl Acetate	5 – 9 %	123-86-4
M.I.B.K.	1– 4 %	108-10-1

N.R.: not regulated – depending on the used products, which are usually nor hazardous.

PRINCIPLE CHARACTERISTICS:

- High weathering, cracking, abrasion, scratching & mechanical resistance
- Good yellowing resistance
- Good gloss retention
- Extreme fast drying
- Fast handling
- Not suitable for immersion in water
- HS code: 3208 10 90

APPLICATION TIPS:

- Air-spray: dilute with 25-35 % of thinner.
- Before applying, the surface must be dry and clean from any contamination.
- Cleaning-up: clean hands and tools with thinner.

PHYSICAL CHARACTERISTICS at 25°C:

- Specific gravity : 1 – 1.2 g/cm³ (water : 1g/cm³)
- Flash point : 30°C
- Boiling point : 70°C <B.P.<120°C
- Viscosity : -
- Solid content : 15 - 25 %
- V.O.C. content : 10 – 20 % (by weight)
- Evaporation rate : slower than butyl acetate
- Vapor pressure : 2.7 – 10.3 mmHg
- Vapor density : heavier than air
- Solubility : soluble in organic solvents
- Solubility in water : < 10 %
- Miscibility with water : not miscible
- Explosion limits : Lower : 1.2 Vol %
Upper : 7.5 Vol%
(it doesn't present any explosion hazard)
- Color : upon BMA solvent based catalogue
- Appearance : heavy liquid
- Odor : turpentine odor
- Touch dry after : 15 minutes
- Hard dry : 1 hour
- Spreading rate : 8 – 10 m²/L

FIRE FIGHTING MEASURES:

- Extinguishing media : - Carbon dioxide
- Waterfog
- Alcohol resistant foam
- Dry chemicals.
- Special procedure : - Evacuate fire area
- Do not enter without fire Resistant suit and special Breathing media.
- Fight fire from a distance due to the threat of pressures in containers which can cause an explosion.

TOXICOLOGICAL AND ECOLOGICAL

INFORMATIONS:

- This product is not established as carcinogen If it's used according to the specifications.
- This product should not reach the ground or the water course - it might accumulate in the water systems (water hazard classification WGK 1).
- In case of moderate exposure, this product is considered having low toxicological effect, except by the ingestion media.

ENVIRONMENT PROTECTION:

- Contain and collect this product leaks with non-flammable and absorbant materials such as sand, soil Dust.
- The empty cans could contain some product residue, which is relatively flammable; get rid of them according to your country regulations.

FIRST AIDS MEASURES:

This product has usually a low toxicity; there is no need for severe safety precaution unless large amounts are absorbed. Although it might have some neurological effect, so it's essential to apply it away from pregnant women and children.

Route of entry	Risk	First aid
Eye contact	Eye irritation after a prolonged exposure	Rinse eyes with large amount of clean water
Skin contact	Skin moderate irritation after a prolonged exposure	Wash the affected zone with soapy water and remove contaminated clothes
Inhalation	Headache, nausea, dizziness, vomiting, narcosis, nose, throat and lungs irritation, only after a prolonged exposure	The affected person should be moved to a very well ventilated area; if the symptoms persist or the breathing stops, an immediate medical care is required
Ingestion	Nausea, vomiting, diarrhea, dizziness and gastrointestinal irritation.	Let the affected person drink a large amount of water, without inducing vomiting; seek a medical care immediately

HEALTH AND SAFETY:

- The Product is flammable; It burns with intense heat. Avoid unnecessary exposure to heat, vapors and travel to source of ignition and flash back.
- Do not smoke while using this product.
- This product is considered having relatively low toxicity, during a short exposure period and a relatively low dose, except by ingestion media.
- Do not eat or drink during the application of this product.
- Keep away from the reach of children.
- Apply away from pregnant women, children and people with respiration problems.

HANDLING AND STORAGE:

- Store in tightly closed containers & keep away from humidity, freezing, direct sunlight, heat, sparks and open flame.
- Apply this product in a well ventilated area, because the released vapors may provoke respiratory irritations.
- Do not hang this product pack on a hook.

TRANSPORT INFORMATION:

- This product is considered as flammable.
- Keep the container well closed and in upright position during transportation.
- IMO class : 3
- UN number : 1263
- Hazard class : flammable liquid 3
- Label : Paint
- Packaging group : II
- Transportation : overland, by air and by sea.

MSDS-COV - H1-13



Produced under license Coverplast – Italy