

DESCRIPTION

Aromatic Isocyanate Hardener.

PRINCIPLE CHARACTERISTICS

- Excellent resistance to atmospheric exposure conditions.
- Excellent gloss retention.
- Non-yellowing.
- Cures at temperatures down to 5 °C.
- Resistance to splash of mineral and vegetable oil, wax, aliphatic petroleum products and mild chemicals.
- Good application properties.

BASIC DATA AT 25°C

Mass density
0.98g/cm³

Flash point
33 °C

Viscosity
110 sec

Storage temperature
10 - 35°C

Shelf life
At least 9 month

Colors
clear

RECOMMENDED SUBSTRAT CONDITION AND TEMPERATURE

- Substrate temperature should be at least 3°C.
- Maximum relative humidity during application and curing is 85%.

CLEAN-UP

Clean hands and tools immediately with thinner polyurethane.
Clean spills right away with a damp cloth.

DIRECTION FOR USE

INSTRUCTION

Well mixing paint with hardener
100:50 by volume .

APPLICATION

CLEANING SOLVENT

Polyurethane Thinner BMA

SAFETY AND HEALTH

In case of eye contact treat any foreign body by flushing with large amounts of water .
For skin contact repeated exposure may cause skin dryness or cracking since , it contains cobalt, ketoxime may cause allergic reaction.
For safety when applying it is advisable to wear eye protection glasses hand gloves and face mask.
Keep out of the reach of children , do not use or store by hanging on a hook.
Lead to toxic exposure that cause serious damage for brain especialy for children and pregnant women.

SHIPPING

Packing

2 L – 2.5 L – 12 L

Storage Condition

Store away from extreme temperature.
Containers should be kept closed during storage.

Limitations

This is a solvent base hardener and care should be taken to avoid inhalation of spray mist or vapor as well as the contact between the hardener and exposed skin or eyes period.

TDS-BMA-E4-B-12

