

**368s - PAINT REMOVER METHYLENE CHLORIDE BASE****Safety data sheet****SECTION 1. Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Code: **368s**  
Product name **PAINT REMOVER METHYLENE CHLORIDE BASE**

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Intended use **Sverniciante**

**1.3. Details of the supplier of the safety data sheet**

Name **MULTICHIMICA SPA**  
Full address **via G. Galilei, 39**  
District and Country **35035 Mestrino (PD)**  
**Italia**  
Tel. **049 9048611**  
Fax **049 9001695**

e-mail address of the competent person responsible for the Safety Data Sheet **lab@multichimica.it**

Product distribution by **Multichimica Spa**

**1.4. Emergency telephone number**

For urgent inquiries refer to **049 9048611**

**SECTION 2. Hazards identification.****2.1. Classification of the substance or mixture.**

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

**2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments.**

Hazard classification and indication:

Carc. 2 H351  
Acute Tox. 4 H302  
STOT RE 2 H373  
Eye Irrit. 2 H319  
Skin Irrit. 2 H315  
STOT SE 3 H335  
STOT SE 3 H336  
STOT SE 2 H371  
Aquatic Chronic 3 H412

**2.1.2. 67/548/EEC and 1999/45/EC Directives and following amendments and adjustments.**

Danger Symbols: Xn

R phrases: 20/21/22-36/38-Carc. Cat. 3 40-48/20-52/53-68/20/21/22

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

## 368s - PAINT REMOVER METHYLENE CHLORIDE BASE

### SECTION 2. Hazards identification. ... / >>

#### 2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Warning

Hazard statements:

<b>H351</b>	Suspected of causing cancer.
<b>H302</b>	Harmful if swallowed.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H336</b>	May cause drowsiness or dizziness.
<b>H371</b>	May cause damage to organs.
<b>H412</b>	Harmful to aquatic life with long lasting effects.

Precautionary statements:

<b>P201</b>	Obtain special instructions before use.
<b>P273</b>	Avoid release to the environment.
<b>P280</b>	Wear protective gloves / protective clothing / eye protection / face protection.
<b>P301+P312</b>	IF SWALLOWED: Call a POISON CENTER or doctor / physician if you feel unwell.
<b>P304+P340</b>	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
<b>P403+P233</b>	Store in a well-ventilated place. Keep container tightly closed.

**Contains:** DICHLOROMETHANE  
METANOLO

#### 2.3. Other hazards.

Information not available.

### SECTION 3. Composition/information on ingredients.

#### 3.1. Substances.

Information not relevant.

#### 3.2. Mixtures.

**Contains:**

Identification.	Conc. %.	Classification 67/548/EEC.	Classification 1272/2008 (CLP).
<b>DICHLOROMETHANE</b>			
CAS. 75-09-2	86 - 90	Carc. Cat. 3 R40, R67, Xn R48/20, Xi R36/37/38	Carc. 2 H351, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, STOT SE 3 H336
EC. 200-838-9			
INDEX. 602-004-00-3			
Reg. no. 01-2119480404-41			
<b>METANOLO</b>			
CAS. 67-56-1	5 - 6	F R11, T R23/24/25, T R39/23/24/25	Flam. Liq. 2 H225, Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, STOT SE 1 H370
EC. 200-659-6			
INDEX. 603-001-00-X			
Reg. no. 01-2119433307-44			
<b>METHYL ETHYL KETONE</b>			
CAS. 78-93-3	1 - 1,5	R66, R67, F R11, Xi R36	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC. 201-159-0			
INDEX. 606-002-00-3			
Reg. no. 01-2119457290-43			

**368s - PAINT REMOVER METHYLENE CHLORIDE BASE****SECTION 3. Composition/information on ingredients. ... / >>****METHANOL**

CAS.	67-56-1	0,8 - 0,9	F R11, T R23/24/25, T R39/23/24/25	Flam. Liq. 2 H225, Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, STOT SE 1 H370
EC.	200-659-6			
INDEX.	603-001-00-X			
Reg. no.	01-2119433307-44			

**TOLUENE**

CAS.	108-88-3	0,6 - 0,7	Repr. Cat. 3 R63, R67, F R11, Xn R48/20, Xn R65, Xi R38	Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336
EC.	203-625-9			
INDEX.	601-021-00-3			
Reg. no.	01-2119471310-51			

**OLIO DI PINO**

CAS.	138-86-3	0,35 - 0,4	Xi R38, Xi R43, N R50/53	Skin Irrit. 2 H315, Aquatic Chronic 1 H410
EC.	266-035-0			
INDEX.	-			

Note: Upper limit is not included into the range.

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

T+ = Very Toxic(T+), T = Toxic(T), Xn = Harmful(Xn), C = Corrosive(C), Xi = Irritant(Xi), O = Oxidizing(O), E = Explosive(E), F+ = Extremely Flammable(F+), F = Highly Flammable(F), N = Dangerous for the Environment(N)

**SECTION 4. First aid measures.****4.1. Description of first aid measures.**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

**4.2. Most important symptoms and effects, both acute and delayed.**

For symptoms and effects caused by the contained substances, see chap. 11.

**4.3. Indication of any immediate medical attention and special treatment needed.**

Information not available.

**SECTION 5. Firefighting measures.****5.1. Extinguishing media.****SUITABLE EXTINGUISHING EQUIPMENT**

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

**5.2. Special hazards arising from the substance or mixture.****HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

**5.3. Advice for firefighters.****GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**368s - PAINT REMOVER METHYLENE CHLORIDE BASE****SECTION 6. Accidental release measures.****6.1. Personal precautions, protective equipment and emergency procedures.**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

**6.2. Environmental precautions.**

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

**6.3. Methods and material for containment and cleaning up.**

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10.

Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**6.4. Reference to other sections.**

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage.****7.1. Precautions for safe handling.**

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire.

Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

**7.2. Conditions for safe storage, including any incompatibilities.**

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

**7.3. Specific end use(s).**

Information not available.

**SECTION 8. Exposure controls/personal protection.****8.1. Control parameters.**

Regulatory References:

United Kingdom

Éire

OEL EU

TLV-ACGIH

EH40/2005 Workplace exposure limits. Containing the list of workplace exposure limits for use with the Control of Substances Hazardous to Health Regulations (as amended).

Code of Practice Chemical Agent Regulations 2011.

Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.

ACGIH 2012

**DICHLOROMETHANE****Threshold Limit Value.**

Type	Country	TWA/8h		STEL/15min		
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	
TLV-ACGIH		174	50			
OEL	IRL	174	20	550	150	SKIN
WEL	UK	350	100	1060	300	SKIN

## 368s - PAINT REMOVER METHYLENE CHLORIDE BASE

### SECTION 8. Exposure controls/personal protection. ... / >>

#### METANOLO

##### Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH		262	200	328	250	SKIN

#### METHYL ETHYL KETONE

##### Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH		590	200	885	300	
OEL	EU	600	200	900	300	
OEL	IRL	600	200	900	300	SKIN
WEL	UK	600	200	899	300	SKIN

#### METHANOL

##### Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH		262	200	328	250	
OEL	EU	260	200			SKIN
OEL	IRL	260	200			SKIN
WEL	UK	266	200	333	250	SKIN

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

### 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

**368s - PAINT REMOVER METHYLENE CHLORIDE BASE****SECTION 9. Physical and chemical properties.****9.1. Information on basic physical and chemical properties.**

Appearance	viscous liquid
Colour	white
Odour	characteristic
Odour threshold.	Not available.
pH.	Not available.
Melting point / freezing point.	Not available.
Initial boiling point.	Not available.
Boiling range.	Not available.
Flash point.	Not available.
Evaporation Rate	Not available.
Flammability of solids and gases	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	1,2 Kg/l
Solubility	Not available.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	2700+/- 400
Explosive properties	Not available.
Oxidising properties	Not available.

**9.2. Other information.**

VOC (Directive 1999/13/EC) :	97,00 %	-	1.164,00	g/litre.
VOC (volatile carbon) :	16,80 %	-	201,64	g/litre.

**SECTION 10. Stability and reactivity.****10.1. Reactivity.**

There are no particular risks of reaction with other substances in normal conditions of use.

DICHLOROMETHANE: decomposes above 120°C. With water and alkalis it may form hydrochloric acid and attack aluminium, copper and alloys.

BUTANONE: reacts with light metals like aluminium, and with strong oxidising agents; attacks various types of plastic. Decomposes under the effect of heat.

**10.2. Chemical stability.**

The product is stable in normal conditions of use and storage.

**10.3. Possibility of hazardous reactions.**

The vapours may also form explosive mixtures with the air.

DICHLOROMETHANE: risk of explosion on contact with alkaline metals, nitric acid, aluminium (powder), ethanediamine, aluminium chloride, perchloric acid, dinitrogen pentoxide, sodium nitride, n-nitroso n-methylurea, potassium hydroxide. Can react dangerously with: alkaline earth metals, metal powders, sodium amides, potassium tert-butylate. Can form explosive mixtures with the air.

BUTANONE: may generate peroxides on contact with air, light or oxidising agents. Risk of explosion on contact with: hydrogen peroxide and sulphuric acid. It may react dangerously with: oxidising agents, trichloromethane, alkalis. Forms explosive mixtures with the air.

**10.4. Conditions to avoid.**

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

DICHLOROMETHANE: avoid exposure to naked flames and hot surfaces.

BUTANONE: avoid exposure to sources of heat.

**10.5. Incompatible materials.**

DICHLOROMETHANE: aluminium, magnesium powder, sodium, potassium, concentrated nitric acid, caustic agents and strong oxidising agents.

BUTANONE: strong oxidising agents, inorganic acids, ammonia, copper and chloroform.

## 368s - PAINT REMOVER METHYLENE CHLORIDE BASE

### SECTION 10. Stability and reactivity. ... / >>

#### 10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

DICHLOROMETHANE: dioxins, phosgenes and hydrochloric acid.

### SECTION 11. Toxicological information.

#### 11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product must be handled carefully because of its possible carcinogenic effects. Anyway, currently available data do not allow us to comprehensively assess this product.

Acute effects: ingestion of this product is harmful. Even small amounts of product may cause serious health problems (stomach pain, nausea, sickness, diarrhoea).

This product may cause functional disorders or morphological mutations after repeated or prolonged exposure and/or may accumulate inside the human body and is thus graded as dangerous.

Acute effects: stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation.

Vapour inhalation may moderately irritate the upper respiratory tract. Contact with skin may cause slight irritation.

Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

Acute effects: contact with skin may cause: irritation, erythema, edema, dryness and chapped skin. Vapour inhalation may slightly irritate the upper respiratory tract. Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

Acute effects: vapour inhalation may irritate the lower and upper respiratory tract and cause cough and respiratory disorders. At higher concentrations it can also cause pulmonary edema. Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

This product contains highly volatile substances, which may cause serious depression of the central nervous system (CNS) and have negative effects, such as drowsiness, dizziness, slow reflexes, narcosis.

This product may cause irreversible, non-lethal damages after a single exposure by inhalation, cutaneous absorption and ingestion.

DICHLOROMETHANE: Acute toxicity in man: cognitive disorders only if inhaled at very high doses; at 200-500 ppm, nausea, vomiting, dizziness, paresthesia, asthenia and headache have been observed. Skin contact causes pain which soon disappears without any burns. Superficial lesions of the cornea occur on contact with the eyes.

METHANOL: The minimal lethal dose following ingestion is considered to be in the range of 300-1000 mg/kg. Ingestion of as little as 4-10 ml methanol in adults may cause permanent blindness (IPCS).

#### DICHLOROMETHANE

LD50 (Oral).	1600 mg/kg Rat
LD50 (Dermal).	> 2000 mg/kg Rat
LC50 (Inhalation).	79 mg/l/2h Rat

#### METHYL ETHYL KETONE

LD50 (Oral).	2737 mg/kg Rat
LD50 (Dermal).	6480 mg/kg Rabbit
LC50 (Inhalation).	23,5 mg/l/8h Rat

#### TOLUENE

LD50 (Oral).	28,1 mg/l 4h rat
LD50 (Dermal).	12124 mg/kg rabbit
LC50 (Inhalation).	28,1 mg/l 4 h rat

#### OLIO DI PINO

LD50 (Oral).	5300 mg/Kg ratto
--------------	------------------

### SECTION 12. Ecological information.

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

#### 12.1. Toxicity.

##### OLIO DI PINO

LC50 - for Fish.	80 mg/l/96h trota iridea
------------------	--------------------------

## 368s - PAINT REMOVER METHYLENE CHLORIDE BASE

### SECTION 12. Ecological information. ... / >>

EC50 - for Crustacea. 17 mg/l/48h daphnia magna

#### 12.2. Persistence and degradability.

DICHLOROMETHANE: not easily biodegradable.

#### 12.3. Bioaccumulative potential.

DICHLOROMETHANE: no appreciable bioaccumulation potential (log Ko/w 1-3).

#### 12.4. Mobility in soil.

DICHLOROMETHANE: very mobile in soil.

#### 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

#### 12.6. Other adverse effects.

Information not available.

### SECTION 13. Disposal considerations.

#### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Avoid littering. Do not contaminate soil, sewers and waterways.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

### SECTION 14. Transport information.

These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations.

These goods must be packed in their original packagings or in packagings made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations.

#### Road and rail transport:

ADR/RID Class:	3	UN:	1263
Packing Group:	III		
Label:	3		
Nr. Kemler:	30		
Limited Quantity:	5 L		
Tunnel restriction code:	(D/E)		
Proper Shipping Name:	PAINT or PAINT RELATED MATERIAL		



#### Carriage by sea (shipping):

IMO Class:	3	UN:	1263
Packing Group:	III		
Label:	3		
EMS:	F-E		, S-E
Marine Pollutant:	NO		
Proper Shipping Name:	PAINT or PAINT RELATED MATERIAL		






## 368s - PAINT REMOVER METHYLENE CHLORIDE BASE

### SECTION 14. Transport information. ... / >>

#### Transport by air:

IATA:	3	UN:	1263	
Packing Group:	III			
Label:	3			
Cargo:				
Packaging instructions:	366	Maximum quantity:	220 L	
Pass.:				
Packaging instructions:	355	Maximum quantity:	60 L	
Special Instructions:	A3, A72			
Proper Shipping Name:	PAINT or PAINT RELATED MATERIAL			

### SECTION 15. Regulatory information.

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category.                      None.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product.

Point.                      3

Contained substance.

Point. <u>                    </u>	48	TOLUENE
		Reg. no.: 01-2119471310-51
Point. <u>                    </u>	59	DICHLOROMETHANE
		Reg. no.: 01-2119480404-41

Substances in Candidate List (Art. 59 REACH).                     

None.

Substances subject to authorisation (Annex XIV REACH).                     

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:                     

None.

Substances subject to the Rotterdam Convention:                     

None.

Substances subject to the Stockholm Convention:                     

None.

Healthcare controls.                     

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

#### 15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

### SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Liq. 2</b>	Flammable liquid, category 2
<b>Carc. 2</b>	Carcinogenicity, category 2
<b>Repr. 2</b>	Reproductive toxicity, category 2
<b>Acute Tox. 3</b>	Acute toxicity, category 3
<b>STOT SE 1</b>	Specific target organ toxicity - single exposure, category 1
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>STOT RE 2</b>	Specific target organ toxicity - repeated exposure, category 2
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>STOT SE 2</b>	Specific target organ toxicity - single exposure, category 2
<b>Aquatic Chronic 1</b>	Hazardous to the aquatic environment, chronic toxicity, category 1
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment, chronic toxicity, category 3
<b>H225</b>	Highly flammable liquid and vapour.
<b>H351</b>	Suspected of causing cancer.

## 368s - PAINT REMOVER METHYLENE CHLORIDE BASE

### SECTION 16. Other information. ... / >>

<b>H361d</b>	Suspected of damaging the unborn child.
<b>H301</b>	Toxic if swallowed.
<b>H311</b>	Toxic in contact with skin.
<b>H331</b>	Toxic if inhaled.
<b>H370</b>	Causes damage to organs.
<b>H302</b>	Harmful if swallowed.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H336</b>	May cause drowsiness or dizziness.
<b>H371</b>	May cause damage to organs.
<b>H410</b>	Very toxic to aquatic life with long lasting effects.
<b>H412</b>	Harmful to aquatic life with long lasting effects.
<b>EUH066</b>	Repeated exposure may cause skin dryness or cracking.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

<b>R11</b>	HIGHLY FLAMMABLE.
<b>R20/21/22</b>	HARMFUL BY INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED.
<b>R23/24/25</b>	TOXIC BY INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED.
<b>R36</b>	IRRITATING TO EYES.
<b>R36/37/38</b>	IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.
<b>R36/38</b>	IRRITATING TO EYES AND SKIN.
<b>R38</b>	IRRITATING TO SKIN.
<b>R39/23/24/25</b>	TOXIC: DANGER OF VERY SERIOUS IRREVERSIBLE EFFECTS THROUGH INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED.
<b>Carc. Cat. 3</b>	Carcinogenicity, category 3.
<b>R40</b>	LIMITED EVIDENCE OF A CARCINOGENIC EFFECT.
<b>R43</b>	MAY CAUSE SENSITISATION BY SKIN CONTACT.
<b>R48/20</b>	HARMFUL: DANGER OF SERIOUS DAMAGE TO HEALTH BY PROLONGED EXPOSURE THROUGH INHALATION.
<b>R50/53</b>	VERY TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.
<b>R52/53</b>	HARMFUL TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.
<b>Repr. Cat. 3</b>	Reproductive toxicity, development, category 3.
<b>R63</b>	POSSIBLE RISK OF HARM TO THE UNBORN CHILD.
<b>R65</b>	HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.
<b>R66</b>	REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING.
<b>R67</b>	VAPOURS MAY CAUSE DROWSINESS AND DIZZINESS.
<b>R68/20/21/22</b>	HARMFUL: POSSIBLE RISK OF IRREVERSIBLE EFFECTS THROUGH INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train

## 368s - PAINT REMOVER METHYLENE CHLORIDE BASE

### SECTION 16. Other information. ... / >>

- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

1. Directive 1999/45/EC and following amendments
2. Directive 67/548/EEC and following amendments and adjustments
3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
4. Regulation (EC) 1272/2008 (CLP) of the European Parliament
5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
6. Regulation (EC) 453/2010 of the European Parliament
7. Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament
8. Regulation (EC) 618/2012 (III Atp. CLP) of the European Parliament
9. The Merck Index. - 10th Edition
10. Handling Chemical Safety
11. Niosh - Registry of Toxic Effects of Chemical Substances
12. INRS - Fiche Toxicologique (toxicological sheet)
13. Patty - Industrial Hygiene and Toxicology
14. N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
15. ECHA website

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

#### Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 06 / 07 / 08 / 09 / 11 / 12 / 14 / 15 / 16.