

**DESCRIPTION**

Fast drying nitrocellulose wood sealer.

**PRINCIPLES CHARACTERISTICS**

- High weathering, cracking and abrasion resistance.
- Excellent sandability.
- Excellent properties.
- Fast drying.
- Fast handling.
- Not suitable for immersion in water.

**BASIC DATA AT 25°C**

**Mass density**

0.90g/cm<sup>3</sup>

**Recommended dry film**

25-35 microns for brush /roller

**Theoretical spreading rate**

8 m<sup>2</sup>/l

**Touch dry after**

15 min. at 25 °C

**Overcoating interval**

4 hrs at 25 °C

**Flash point**

30 °C

**Viscosity**

350 poises

**Solid content**

52%

**Hard dry**

To sand 1 hour

**Storage temperature**

10 - 35°C

**Shelf life**

24 month

**Full cure**

4 - 5 hours

**Colors and Gloss**

Pale yellow - matt

## RECOMMENDED SUBSTRAT CONDITION AND TEMPERATURES

- Wood should be dry & clean from any contamination.
- Prepared wood.
- Substrate temperature should be at least 10 °C.

### **CLEAN-UP**

Clean hands and tools immediately with NC thinner.  
Clean spills right away with a damp cloth.

## DIRECTION FOR USE

### **INSTRUCTION**

- Well mixing sealer with NC thinner to get application viscosity.

### **APPLICATION**

#### BRUSH/ROLLER

Recommended solvent :NC Thinner BMA  
Percentage of solvent :10-15%

#### AIR SPRAY

Recommended solvent :NC Thinner BMA  
Percentage of solvent :150-200% depending on Application viscosity.

#### CLEANING SOLVENT

NC Thinner BMA

## SAFETY AND HEALTH

In case of eye contact treat any foreign body by flushing with large amounts of water .  
For skin contact repeated exposure may cause skin dryness or cracking since , it contains cobalt, ketoxime may cause allergic reaction.  
For safety when applying it is advisable to wear eye protection glasses hand gloves and face mask.  
Keep out of the reach of children , do not use or store by hanging on a hook.  
Lead to toxic exposure that cause serious damage for brain especialy for children and pregnant women.

## SHIPPING

<b>Packing</b>	<b>Storage Condition</b>	<b>Limitations</b>
US gallon- 20 L	Store away from extreme temperature. Containers should be kept closed during storage.	This is a solvent base paint and care should be taken to avoid inhalation of spray mist or vapor as well as the contact between the wet paint and exposed skin or eyes period.

TDS-BMA-F1-B-12

