

DESCRIPTION

Water borne sanding paint based on styrene acrylic for isolation purpose .

PRINCIPLE CHARACTERISTICS

- Particularly suitable when solvents are not permitted because of health and safety reasons.
- Easy application by roll or brush with excellent flow.
- Good weathering resistance.
- High opacity.
- Excellent isolation , adhesion properties .
- High durability.
- Can be washed with soap and water.
- It includes granulated gravels.

BASIC DATA AT 25°C**Mass density**

1.25 g /cm³ (white)

Recommended dry film

90 microns per coat

Theoretical spreading rate

8-10 m²/l for white

Touch dry after

2 hr. depending on the temperature & humidity

Overcoating interval

24 hours at 25 °C

Flash point

Above 65 °C

Viscosity

33 poises

Solid content

43 %

Shelf life

at least 24 months

Colors and Gloss

White – red brick(other colors on request)- semi gloss.

Full cure

72 hours

RECOMMENDED SUBSTRAT CONDITIONS AND TEMPERATURES

- Previous mortared cementitious walls.
- Primed wall with putty.
- Substrate temperature should be at least 10 °C .
- Preferably relative humidity should not exceed 75%.

CLEAN-UP

Clean hands and tools immediately with water.
Clean spills right away with a damp cloth.

DIRECTIONS FOR USE

INSTRUCTIONS

- First clean the surface very well with soapy water , let it completely dry then remove the dust ; all of this must be in sunny day .
- Dilute the product with 60 % of tap water and apply the first layer using a roll then let it one hour .
- Dilute the product with 25 % of tap water to apply the second layer .
- After 72 hours , apply one coat of clear bond to get more isolation properties for a long periode.

APPLICATION

BRUSH/ROLLER

Recommended solvent : tap water
Percentage of solvent : 25 – 60 %

CLEANING SOLVENT

Tap water

SAFETY AND HEALTH

In case of eye contact treat any foreign body by flushing with large amounts of water . For skin contact repeated exposure may cause skin dryness or cracking since , it contains cobalt, ketoxime may cause allergic reaction. For safety when applying it is advisable to wear eye protection glasses hand gloves and face mask.

Keep out of the reach of children , do not use or store by hanging on a hook.

Lead to toxic exposure that cause serious damage for brain especially for children and pregnant women.

SHIPPING

Packing

US gallon- 17 L

Storage Condition

Store away from extreme temperature.
Containers should be kept closed during storage.

Limitations

This is a water base product although care should be taken.