

DESCRIPTION

One component , fast air - drying , nitrocellulose wood & steel paint.

PRINCIPLE CHARACTERISTICS

- High weathering , cracking & abrasion resistance.
- Good yellowing resistance.
- Suitable for interior & exterior use over any wood or steel surface .
- Good gloss retention.
- Fast drying.
- Fast handling.
- Not suitable for immersion in water.

BASIC DATA AT 25°C**Mass density**

1.20g/cm³ (white)-1.10g/cm³(other colors)

Recommended dry film

25-35 microns for brush

Theoretical spreading rate

8-10 m²/l

Touch dry after

15 min. at 25 °C

Overcoating interval

2hrs at 25 °C

Flash point

30 °C

Viscosity

28poises(white)-25poises(other colors)

Solid Content

32-48 %

Hard dry

3 hours

Storage temperature

10 - 35° C

Shelf life

24 months

Colors and gloss

All the basic colors (other colors upon request) - glossy ; semigloss;30% gloss ; matt

Full cure

4 hours

RECOMMENDED SUBSTRAT CONDITION AND TEMPERATURE

- Seal surface that should be dry & clean from any contamination.
- Prepared ferrous metals , dry and free from contaminations.
- Primed and sanded wood with NC sealer.
- Substrate temperature should be at least 10 °C.

CLEAN-UP

Clean hands and tools immediately with thinner.
Clean spills right away with a damp cloth.

DIRECTION FOR USE

INSTRUCTION

- Well mixing paint with thinner to get application viscosity.
- For semi matt ; 30%gloss & matt paint stir well before use.

APPLICATION

BRUSH/ROLLER

Recommended solvent :NC Thinner BMA
Percentage of solvent :10-15%

AIR SPRAY

Recommended solvent : Nitro Thinner BMA
Percentage of solvent : 25-35% depending on Application viscosity.

CLEANING SOLVENT

NC Thinner BMA

SAFETY AND HEALTH

In case of eye contact treat any foreign body by flushing with large amounts of water .
For skin contact repeated exposure may cause skin dryness or cracking since , it contains cobalt, ketoxime may cause allergic reaction.
For safety when applying it is advisable to wear eye protection glasses hand gloves and face mask.
Keep out of the reach of children , do not use or store by hanging on a hook.
Lead to toxic exposure that cause serious damage for brain especialy for children and pregnant women.

SHIPPING

Packing

US gallon- 20 L

Storage Condition

Store away from extreme temperature.
Containers should be kept closed during storage.

Limitations

This is a solvent base paint and care should be taken to avoid inhalation of spray mist or vapor as well as the contact between the wet paint and exposed skin or eyes period.