

DESCRIPTION

It is a decorative acrylic finish that can be water base or solvent base.

PRINCIPLES CHARACTERISTICS

- Particularly suitable when solvents are not permitted because of health and safety reasons .
- Easy application by brush or sponge with excellent flow.
- Excellent adhesion properties.
- Suitable drying time for application.
- Excellent durability.
- Excellent weathering properties.

BASIC DATA AT 25°C

Mass density
1g /cm³ (white)

Recommended dry film
30 microns per coat

Theoretical spreading rate
8 m²/l for white

Touch dry after
1 hour depending on the temperature & humidity

Overcoating interval
3 – 4 hours at 25 °C

Flash point
Above 65 °C

Viscosity
14 poises

Solid content
20 – 22 %

Storage Temperature
10-35°C

Shelf life
At least 24 months

Colors and Gloss
Clear, semigloss, gloss-Colors are available upon BMA catalogues (other colos upon request).

Full cure
6 hours

RECOMMENDED SUBSTRAT CONDITION AND TEMPERATURES

- Previous primed silky paint.
- Primed wall with putty then rubber or acrylic water base .
- Substrate temperature should be at least 10°C .
- Preferably relative humidity should not exceed 75%.

CLEAN-UP

Clean hands and tools immediately with tap water if it's water base, White spirit if it's solvent base.
Clean spills right away with a damp cloth.

DIRECTION FOR USE

INSTRUCTION

- Color and mix well before use.
- The temperature of the paint should preferably be above 15 °C, otherwise Extra Tap water or W.S may be required to obtain application viscosity.
- Too much solvent (water or w.s.) result in reducing sag resistance and opacity.
- Must be protected from freezing at all times during storage.

APPLICATION

BRUSH/ROLLER/SPONGE

Recommended solvent : Tap water(if it's w.base), White spirit (if it's solvent base)
Percentage of solvent : 0 - 5%

CLEANING SOLVENT

Tap water or white spirit .

SAFETY AND HEALTH

In case of eye contact treat any foreign body by flushing with large amounts of water .

For skin contact repeated exposure may cause skin dryness or cracking ;also it may cause allergic reaction.

For safety when applying it is advisable to wear hand gloves.

Keep out of the reach of children , do not use or store by hanging on a hook.

Lead to toxic exposure that cause serious damage for brain especialy for children and pregnant women.

SHIPPING

Packing

1L-US gallon- 17 L

Storage Condition

Store away from extreme temperature.
Containers should be kept closed during storage.

Limitations

This is a water /solvent base paint and care should be taken.

TDS-BMA-B8-B-12

