

#### DESCRIPTION

Fast drying nitrocellulose hammer based paint.

#### PRINCIPLES CHARACTERISTICS

- High weathering , cracking , abrasion & mechanical resistance.
- Good yellowing resistance.
- Good gloss retention.
- Fast drying.
- Fast handling.
- Not suitable for immersion in water.

#### BASIC DATA AT 25°C

**Mass density**

1.0 g/cm<sup>3</sup>

**Recommended dry film**

25-35 microns for brush

**Theoretical spreading rate**

8-10 m<sup>2</sup>/L

**Touch dry after**

15 min. at 25 °C

**Overcoating interval**

2hrs at 25 °C

**Flash point**

30 °C

**Viscosity**

40 poises

**Solid Content**

38-39%

**Hard dry**

3 hours

**Storage temperature**

10 - 35° C

**Shelf life**

24 months

**Colors and gloss**

Metallic - other colors upon request

**Full cure**

4 hours

## RECOMMENDED SUBSTRAT CONDITION AND TEMPERATURES

- Substrate temperature should be at least 10 °C.
- Prepared ferrous metals that should be dry and free from any contamination.
- Steel surface that should be dry & clean from any contamination.

### **CLEAN-UP**

Clean hands and tools immediately with NC thinner.  
Clean spills right away with a damp cloth.

## DIRECTION FOR USE

### **INSTRUCTION**

- Well mixing paint with thinner to get application viscosity.
- Apply one or two coats of primer on aluminium galvanized .
- Surface precoated with two pack of wash primer to improve adhesion.

### **APPLICATION**

#### BRUSH/ROLLER

Recommended solvent :Nitro Thinner BMA  
Percentage of solvent :10-15%

#### AIR SPRAY

Recommended solvent :Nitro Thinner BMA  
Percentage of solvent :25-35% depending on  
Application viscosity.

#### CLEANING SOLVENT

NC Thinner BMA

## SAFETY AND HEALTH

In case of eye contact treat any foreign body by flushing with large amounts of water .  
For skin contact repeated exposure may cause skin dryness or cracking since , it contains cobalt, ketoxime may cause allergic reaction.  
For safety when applying it is advisable to wear eye protection glasses hand gloves and face mask.  
Keep out of the reach of children , do not use or store by hanging on a hook.  
Lead to toxic exposure that cause serious damage for brain especialy for children and pregnant women.

## SHIPPING

### **Packing**

US gallon

### **Storage Condition**

Store away from extreme temperature.  
Containers should be kept closed during storage.

### **Limitations**

This is a solvent base paint and care should be taken to avoid inhalation of spray mist or vapor as well as the contact between the wet paint and exposed skin or eyes period.