

DESCRIPTION

Water borne texture paint based on copolymer acrylic.

PRINCIPLES CHARACTERISTICS

- Good adhesion.
- Easy application and workability.
- Suitable for internal and external application.
- Excellent weathering resistance.
- Excellent resistance to color retention.
- High durability.
- High build film.

BASIC DATA AT 25°C

Mass density

1.76 g/cm³

Recommended dry film

100-120 microns per coat

Theoretical spreading rate

0.75-1 kg/m²

Touch dry after

4 hr. depending on temperature, humidity.

Overcoating interval

12 hrs at 25 °C

Flash point

Above 65 °C

Viscosity

200 poise

Solid content

73-75%

Storage temperatures

10 - 35° C

Shelf life

At least 12 months

Colors and Gloss

Colors available upon BMA catalogue (other colors upon request) – flat.

Full cure

24 hours

RECOMMENDED SUBSTRAT CONDITION AND TEMPERATURES

- previous mortared cementitious walls.
- Previous clear bond or roof coating primed wall.
- Substrate temperature should be at least 10 °C .

CLEAN-UP

Clean hands and tools immediately
With tap water.
Clean spills right away with a damp cloth.

DIRECTION FOR USE

INSTRUCTION

- Applying by suitable roller.
- The temperature of the paint should preferably be above 15°C, otherwise extra tap water may be required to obtain application viscosity.
- Must be protected from freezing at all times during storage .

APPLICATION

ROLLER

Recommended solvent : Tap water
Percentage of solvent : 0-5 %

CLEANING SOLVENT

Tap water

SAFETY AND HEALTH

In case of eye contact treat any foreign body by flushing with large amounts of water .
For skin contact repeated exposure may cause skin dryness or cracking ;also it may cause allergic reaction.
For safety when applying it is advisable to wear hand gloves.
Keep out of the reach of children , do not use or store by hanging on a hook.
Lead to toxic exposure that cause serious damage for brain especially for children and pregnant women.

SHIPPING

Packing

17 L

Storage Condition

Store away from extreme temperature.
Containers should be kept closed during storage.

Limitations

This is a water base paint although care should be taken.

