

## DESCRIPTION

Water borne texture paint based on copolymer acrylic mixed with coarse sand.

## PRINCIPLES CHARACTERISTICS

- Good adhesion.
- Easy application and workability.
- Suitable for internal and external application.
- Excellent weathering resistance.
- Excellent resistance to color retention.
- High durability.
- High build film.

## BASIC DATA AT 25°C

### Mass density

1.99 g/cm<sup>3</sup>

### Recommended dry film

100-120microns/coat.

### Theoretical spreading rate

2-2.5 kg/ m<sup>2</sup>

### Touch dry after

4 hr. depending on the temperature & humidity

### Overcoating interval

12 hours at 25°C

### Flash point

above 65°C

### Viscosity

200 poise

### Solid content

80 %

### Storage Temperature

10-35°C

### Shelf life( cool & dry place)

At least 12 months

### Colors and Gloss

Colors are available upon BMA catalogues( other colos upon request)-flat.

### Full cure

24 hours

## RECOMMENDED SUBSTRAT CONDITION AND TEMPERATURES

- previous mortared cementitious walls
- Previous clear bond or roof coating primed wall.
- Substrate temperature should be at least 10 °C

### **CLEAN-UP**

Clean hands and tools immediately with tap water.  
Clean spills right away with a damp cloth.

## DIRECTION FOR USE

### **INSTRUCTION**

- Applying by suitable Roller.
- The temperature of the paint should preferably be above 15°C, otherwise extra tap water may be required to obtain application viscosity.
- Must be protected from freezing at all times during storage .

### **APPLICATION**

#### ROLLER

Recommended solvent : Tap water  
Percentage of solvent : 0-5%

#### CLEANING SOLVENT

Tap water

## SAFETY AND HEALTH

In case of eye contact treat any foreign body by flushing with large amounts of water .  
For skin contact repeated exposure may cause skin dryness or cracking ;also it may cause allergic reaction.  
For safety when applying it is advisable to wear hand gloves.  
Keep out of the reach of children , do not use or store by hanging on a hook.  
Lead to toxic exposure that cause serious damage for brain especially for children and pregnant women.

## SHIPPING

### **Packing**

17 L

### **Storage Condition**

Store away from extreme temperature.  
Containers should be kept closed during storage.

### **Limitations**

This is a water base paint although care should be taken.

TDS-BMA-B6-A-12

