

**DESCRIPTION**

Water borne , texture paint , based on a copolymer acrylic resin and including the finest grinded quartz rocks .

It gives the walls a sanding textured finish .

**PRINCIPLE CHARACTERISTICS**

- Good adhesion.
- Easy application and workability .
- Suitable for internal application and external application.
- Excellent weathering resistance.
- Excellent color retention.
- High durability.
- High build film.
- Great coverage property , with an excellent flow .
- Could be directly applied over any cementitious or mortared wall ,which is primed or not with a water base putty or a with one or more coat of roll mohair , roll sanding or miniplexine special primer .
- Could be protected by a clear bond layer .

**BASIC DATA AT 25°C****Mass density**

1.99 g/cm<sup>3</sup>

**Recommended dry film**

1l/meter for one layer

**Theoretical spreading rate**

2-2.5Kg/ m<sup>2</sup>

**Touch dry after**

3hr. depending on the temperature & humidity

**Overcoating interval**

6 hours at 25°C

**Flash point**

above 65°C

**Viscosity**

200 poises

**Solid content**

75 %

**VOC Content**

0.8 – 1.2 %

**Hard Dry**

3-7 hours

**Storage Temperature**

10-35°C

**Shelf life( cool & dry place)**

At least 12 months

**Colors and Gloss**

Colors are available upon BMA catalogues ( other colos upon request) - flat.

**Full cure**

24 hours

## APPLICATION

Well clean the wall or the ceiling , rub it with a rubbing stone to unify the surface , leaving an almost coarse texture in order to improve the adhesion .

Treat the surface with a silicone oil solution which protects it against humidity and leaking .

Apply one coat of water base sealer , 2 coats of BMA extra fill putty then 1 coat of ultra fine putty and rub it with a 150 – 180 grit of sanding paper , before applying 1 or 2 coats of a textured primer for miniplexine , a roll mohair or a roll sanding .

After total dryness , apply one thick coat of miniplexine then finalize with a clear bond top coat.

## DIRECTION FOR USE

### Instructions

- Apply by a suitable blade or spatula .
- Could be applied by a roller .
- the temperature of the paint should preferably be above 15°C , otherwise extra tap water may be required to obtain application viscosity.
- Must be protected from freezing at all times during storage.
- Substrate temperature should be at least 10 °C .

### Dilution and Cleaning – up

#### BLADE/SPATULA

Recommended thinner : tap water

Percentage of water : 0 - 3 % if necessary

#### CLEANING SOLVENT

Clean hands and tools immediately with tap water.

Clean spills right away with a damp cloth.

## SAFETY AND HEALTH

In case of eye contact treat any foreign body by flushing with large amounts of water .

For skin contact repeated exposure may cause skin dryness or cracking ;also it may cause allergic reaction.

For safety when applying it is advisable to wear hand gloves.

Keep out of the reach of children , do not use or store by hanging on a hook.

Lead to toxic exposure that cause serious damage for brain especialy for children and pregnant women.

## SHIPPING

### Packing

19 L

### Storage Condition

Approximatively 12 months in sealed container under cool frost - free conditions . Protect from heat and direct sunlight.

### Limitations

This is a water base paint although care should be taken.

TDS-BMA-B7-b-13

