

DESCRIPTION

Mix between hydrocarbon and ethylene glycol.

PRINCIPLES CHARACTERISTICS

Used as a diluent for epoxy paints and lacquers.

BASIC DATA AT 25°C

Mass density

0.88 g /cm³

Flash point

20 °C

Storage temperature

5°C - 35° C

Boiling Point

135° C

Shelf life

3-4 years

Color

clear

RECOMMENDED SUBSTRAT CONDITION AND TEMPERATURES

- Substrate temperature should be at least 10°C .
- Preferably relative humidity should not exceed 75%.

DIRECTION FOR USE

INSTRUCTION

- The temperature should preferably be between 5°C - 35°C.
- keep this material away from firing sources.

SAFETY AND HEALTH

In case of eye contact treat any foreign body by flushing with large amounts of water . For skin contact repeated exposure may cause skin dryness or cracking since , it contains materials that may cause allergic reaction. For safety when applying it is advisable to wear eye protection glasses hand gloves and face mask.

Extreme care should be taken while moving this material .

Keep out of the reach of children , do not use or store by hanging on a hook.

Lead to toxic exposure that cause serious damage for brain especialy for children and pregnant women.

SHIPPING

Packing

All packages are available upon request.

Storage Condition

Store away from extreme temperature.
Containers should be kept closed during storage.

Limitations

This is a solvent base paint and care should be taken to avoid inhalation of spray mist or vapor as well as the contact between the wet paint and exposed skin or eyes period.

TDS-BMA-D3-12

