

DESCRIPTION

Butyl ether of ethylene glycol , comonly used as a solvent in paints and cleaning products .

PRINCIPLES CHARACTERISTICS

- Solvent for spray lacquers, quick dry lacquers , enamels , varnishes , latex paints , thinners , varnish removers and resins .
- Solvent for inks.
- Degreaser for industrial and household detergents .

BASIC DATA AT 25°C

Mass density

0.90 g /cm³ .

Flash point

60°C

Boiling point

172° C

Shelf life

3-4 years

Storage temperature

5°C - 35° C

Colors

Clear .

RECOMMENDED SUBSTRAT CONDITION AND TEMPERATURES

- Storage must be in dry place .
- Preferably relative humidity should not exceed 75%.

DIRECTION FOR USE

INSTRUCTION

- The temperature should preferably be between 5°C - 35°C.
- keep this material away from firing sources.

SAFETY AND HEALTH

In case of eye contact treat any foreign body by flushing with large amounts of water .
For skin contact repeated exposure may cause skin dryness or cracking since , it contains materials that may cause allergic reaction.
For safety when applying it is advisable to wear eye protection glasses hand gloves and face mask.
Extreme care should be taken while moving this material .
Keep out of the reach of children , do not use or store by hanging on a hook.
Lead to toxic exposure that cause serious damage for brain especialy for children and pregnant women.

SHIPPING

| Packing | Storage Condition | Limitations |
|--|--|--|
| All packages are available upon request. | Store away from extreme temperature. Containers should be kept closed during storage. | This is a solvent base product and care should be taken to avoid inhalation of spray mist or vapor as well as the contact between the solvent and exposed skin or eyes period. |