

DESCRIPTION

Aromatic Isocyanate Hardener for cap paint primers.

PRINCIPLES CHARACTERISTICS

- High weathering, cracking and abbrasion resistance.
- Fast drying.
- Fast handling.
- High durability.
- Not suitable for immersion in water.

BASIC DATA AT 25°C

Mass density

0.89g/cm³

Flash point

20 °C

Viscosity

40 – 50 sec

Solid Content

47 %

Storage temperature

10 - 35°C

Shelf life

9 months

Colors

clear

RECOMMENDED SUBSTRAT CONDITION AND TEMPERATURES

- Wood surface should be dry, cleaned from contamination.
- Prepared wood by sanding it with suitable sandpaper.
- Substrate temperature should be at least 10 °C.

CLEAN-UP

Clean hands and tools immediately with thinner polyurethane.
Clean spills right away with a damp cloth.

DIRECTION FOR USE

INSTRUCTION

- Well mixing paint with hardener (100:25)

APPLICATION

CLEANING SOLVENT

Polyurethane Thinner BMA

SAFETY AND HEALTH

In case of eye contact treat any foreign body by flushing with large amounts of water . For skin contact repeated exposure may cause skin dryness or cracking since , it contains cobalt, ketoxime may cause allergic reaction. For safety when applying it is advisable to wear eye protection glasses hand gloves and face mask.

Keep out of the reach of children , do not use or store by hanging on a hook.

Lead to toxic exposure that cause serious damage for brain especialy for children and pregnant women.

SHIPPING

Packing

5L gallon- 1 L - 350 ml

Storage Condition

Store away from extreme temperature.
Containers should be kept closed during storage.

Limitations

This is a solvent base hardener and care should be taken to avoid inhalation of spray mist or vapor as well as the contact between the hardener and exposed skin or eyes