



HARDENER LACQUER 2K

HPU500

DESCRIPTION

Aromatic Isocyanate Hardener for car lacquer.

BASIC DATA AT 25°C

Mass density

0.89g/cm³

Flash point

20 °C

Viscosity

40 – 50 sec

Storage temperature

10 - 35°C

Shelf life

At least 9 months

Colors

clear

PRINCIPLES CHARACTERISTICS

- High weathering, cracking and abbrasion resistance .
- Fast drying.
- Fast handling.
- High durability.
- Not suitable for immersion in water.

RECOMMENDED SUBSTRAT CONDITION AND TEMPERATURES

- Surface should be dry, cleaned from contamination.
- Prepare the surface by sanding it with suitable sandpaper.
- Substrate temperature should be at least 10 °C.

CLEAN-UP

Clean hands and tools immediately with thinner polyurethane or 2K.
Clean spills right away with a damp cloth.

DIRECTION FOR USE

INSTRUCTION

- Well mixing paint with hardener (100:25)

APPLICATION

CLEANING SOLVENT
Thinner 2K BMA

SAFETY AND HEALTH

In case of eye contact treat any foreign body by flushing with large amounts of water .
For skin contact repeated exposure may cause skin dryness or cracking since , it contains cobalt, ketoxime may cause allergic reaction.
For safety when applying it is advisable to wear eye protection glasses hand gloves and face mask.
Keep out of the reach of children , do not use or store by hanging on a hook.
Lead to toxic exposure that cause serious damage for brain especialy for children and pregnant women.

SHIPPING

Packing

1 L - 250 ml

Storage Condition

Store away from extreme temperature.
Containers should be kept closed during storage.

Limitations

This is a solvent base hardener and care should be taken to avoid inhalation of spray mist or vapor as well as the contact between the hardener and exposed skin or eyes.